

Intermol TTC

Technical Datasheet

GENERAL DESCRIPTION

The automotive industry requires a tire that does not present vibrations, noise, imbalance, lateral traction, irregular and excessive wear. For efficient mounting of the rim, it must be guaranteed that it maintains its perfectly round and homogeneous geometry, which requires a high degree of uniformity. To obtain the best possible results in conjunction with assembly machines, it is necessary for the lubricant to provide the best sliding properties and reduction of friction between the tool, the tire and the rim.

Intermol TTC is a paste of natural origin, its ingredients allow it to offer a high reduction in friction in the rubber-metal contact, it also provides a high film resistance and provides high anticorrosive protection without generating reactions with uncoated Iron and Aluminum wheels.

APPLICATION

Tire mounting machinery, balancing machines and uniformity measuring machines, can also be used in mounting hoses, bushings and other automotive rubber parts. The product is delivered ready to use, however dilutions can be made with water to reduce its consistency.

INSTRUCTIONS

Apply a homogeneous film on the bead area and the lower area of the rim on the outer side.

To obtain an optimal sliding, a thin film should be applied without excess, which can be applied with a brush, sponge or roller on the inner bead of the rim.

It does not contain solvents or silicones, being water-based it evaporates in a short time although the lubricating film continues to work.

PRECAUTIONS

Keep the product covered in its original container, store indoors, avoid direct contact with water during the use of the product and its storage. This can affect the efficiency of the product, as well as exposure to low temperatures.


CONTACT

servicio@intermol.com.mx
Tel: (+52 33) 3793 8800

Lateral Sur Periférico Norte 559
Parque Industrial Belenes Norte
C.P. 45150
Zapopan, Jal. México

Legal and safety information, www.intermol.com.mx/disclaimer

APPEARANCE



Name: Intermol TTC
Type: Lubricant paste
Color: Semi-transparent Amber
Ready to Use

APPLICATION



Rubber

CHARACTERISTICS

Specific Gravity: 1.0
Base: Water
Shelf life: 12 months
Temperature Range: °C



STRENGTHS



Water Based



Silicone free